

CM ENGRAVE

JOHN SMITH

VALVE

000 000000

WW-17-VAV-09

WW-12-VAV-07

LAMICOID TAGS  
CORNERS NOTCHED  
HOLES DRILLED

Hope you enjoy your new home

“Agents Name”

SIGNAGE & LAMICOIDS

CM ENGRAVE

SPRINKLER  
CONTROL  
VALVE

44

LIGHTING RETROFIT

09/06/10

ELECTRICAL RATING

Voltage - 347v  
Amperage - 0.30 amps  
Wattage - 70 Watts

PANEL FEED  
12345678

43

EQUIPMENT DETAILS

Name: Bin Washing Station

ID: BWS 009

Location: Room 212

Manufacturer: Canaan Technology

Model: MD-2000

Capacity: 1700L

45

SIGNAGE & LAMICOIDS

CM ENGRAVE



*Polar Rovers*

MECHANICAL ROOM  
EF-1

SPRINKLER  
CONTROL  
VALVE

Personal, Corporate, Industrial Lamicoids,  
Plastic & Metal, Plaques, Annuals,  
Name Tags, Signage



SIGNAGE & LAMICOIDS

CM ENGRAVE

THIS ALARM IS ONLY LOCAL IN CASE OF FIRE PHONE

911

45

Weather Proof Plastic

EQUIPMENT DETAILS

Name: Bin Washing Station ID: BWS 009  
Location: Room 212  
Manufacturer: Canaan Technology  
Model: MD-2000

Laser Cut

46

SIGNAGE

44

WW-12-VAV-07



43

UNDERGROUND CONDUCTORS

CIRCUIT I.D. FEED FROM CSTE  
YEAR INSTALLED 2011  
DIAGRAM B4-1 DETAIL 1 TABLE D8B  
SIZE/TYPE OF CONDUCTOR 350 MCM CU  
AMPACITY 450A MAX. OVERCURRENT 400A

47

- PANEL C cct. 42
- PANEL C cct. 40
- PANEL C cct. 64
- PANEL C cct. 74
- PANEL C cct. 76
- PANEL C cct. 38
- PANEL C cct. 36
- PANEL C cct. 78
- PANEL C cct. 1
- PANEL C cct. 1
- PANEL C cct. 1
- PANEL C cct. 1
- PANEL C cct. 1
- PANEL C cct. 1

**CLARK** From the factory this truck meets ASME B56.1

Authorization No. \_\_\_\_\_


Type \_\_\_\_\_ Serial No. \_\_\_\_\_

C	D	A		
D/Tire Width	in	mm		
D/Tire Type			B	

indicated by dimensions D.

Truck Weight	lb or	kg	Max Battery	lb or
Electric truck in without Battery			Min Battery	lb or
Max. Amp Hrs.			Volts	Battery Type

Made in Korea For other capacities consult Clark Material Handling Co. Lexington, KY 8032189



SIGNAGE & LAMICOIDS

# CM ENGRAVE

**ELECTRICS CORPORATION**

DRY TYPE  
TRANSFORMER  
CLASS AA/FFA

KVA	3000	3 PHASE	HERTZ	60	%IZ	9.66	°C RISE	150
H.V.	13800 $\Delta$	95 KV BILL	AMPS	126	WGT.	14800 (C&C)	LBS.	
L.V.	4160Y/2400	30 KV BILL	AMPS	416	NO.	A69275		

2 / 12 HVUS15 CMV3000MD - 4 200090 - 01 - 01

H.V TAP	VOLTS
1 - 2	14490
2 - 3	14145
1 - 4	13800
3 - 4	13455
4 - 5	13110
5 - 6	

POLARITY

LOW VOLTAGE

DE - ENERGIZE TRANSFORMER BEFORE CHARGING TAPS NP - 310

<b>6</b>	SERIAL No. <b>20121050</b>
der Coat Oven	DATE <b>10/18/2012</b>
PH. <b>1</b>	AMPS <b>105a</b>
<b>120vac. 24vac. 24vdc.</b>	

FUEL TYPE <b>Nat. Gas</b>	BTU'S <b>745,000</b>
SUPPLY PRES. <b>3.5 inches</b>	MIN. MANIFOLD PRES. <b>2 inches</b>
MAX. MANIFOLD PRES. <b>3.5</b>	MAX. OVEN TEMP <b>500 deg</b>
EXHAUST FAN CFM <b>1200</b>	MAKEUP AIR CFM <b>4500</b>
PURGE TIME <b>2 min.</b>	RECIRC. FAN CFM <b>1200</b>
PUMP #1 GPM <b>73</b>	MAX. SPRAY PRES. <b>5 psi</b>
PUMP #2 GPM <b>73</b>	MIN. SPRAY PRES. <b>2 psi</b>

## SIGNAGE & LAMICOIDS